

Linear Technology Korea

Tel. 02-792-1617
Email. kwkim@linear.com

/ Perrien Worldwide
Tel. 017-427-8279 (02-812-1144)
Email. desiree@perrien.co.kr

, 60V, 1.4A (I_{sw}) 200kHz
100uA,

DC/DC
140°C

2005 8 1 -

(, www.linear.com)가 LT1976

'H-Grade'

. LT1976

60V

(Burst Mode®)

100uA

. 'H'

140°C

, 'E' 'I'

125°C

가

. 'H'

140°C

가

LT1976

가 3.3V ~ 60V

(load dump)

(cold-crank)

. 1.5A

1.25V

1.25A

가 100uA ,

' (on)'

LT1976HFE TSSOP-16E

가

가 1

4.85

LT1976H

- : 140°C
- : 3.3V ~ 60V
- 1.5A
- : 100uA
- : IQ <1uA
- (Power Good Flag)
- 60V 가
- 200kHz
- : 0.2
-
- 1.25V
-
-
- 16 TSSOP

1981 IC 가
, DC-DC , , RF ,
(,), / , ,
, (MP3), ,
가

Doug Dickinson, Media Relations Manager
Linear Technology Corporation
1630 McCarthy Boulevard, Milpitas, CA 95035-7417, ddickinson@linear.com, 408-432-1900

: 1-800-4-LINEAR ()
<http://www.linear.com>

: LT, LTC, Burst Mode  Linear Technology Corp.